



Samsung OfficeServ 7070 is an IP-PBX optimized for small and medium sized businesses having less than 50 employees. It supports not only VoIP communications, but works perfectly with existing communication infrastructures. Moreover, it provides powerful performance with built-in functions that are essential for small and medium-sized businesses such as CID, Auto Attendant, and Voice Mailing Service.

Features

Easy Installation

- Supports all the call functions of the existing PBX
- Full compatibility with the OfficeServ 7000 series using identical S/W and terminals
- A single, wall-mounted cabinet structure
- Scalability of multiple service boards into the universal slot
- A refined design suitable for small and medium-sized offices

Scalability

- Various line groups can be configured through expansion in 4-line units
- Supports Spnet connectivity with the OfficeServ 7000 series

VoIP Support

- Supports 8 VoIP channels without additional equipment
- Reduces communication costs by working together with Internet telephony service providers through
- Provides teleworking solutions through an IP network
- An integrated VoIP network can provide seamless collaboration with a remote office

Built-in Applications

- Supports Voice Mail, Auto Attendant, and CID function without additional equipment
- Equipped with Internal MOH, External MOH, Paging, and Contact

Various terminals and differential points

OfficeServ 7400 has the function of fax and can make an emergency call (911) in the case of electric p

SOA(Service Oriented Architecture)-based Business Solutions

Supports interworking with solutions such as the IP contact center, groupware, video conference call, etc.
Provides the OpenAPI to allow interworking with third party solutions, helping the customer's business

User-friendly Terminal Lineup

Samsung OfficeServ supports IP UMS that provides you unified messaging service of telephone, IP Phone, etc.

SOA(Service Oriented Architecture)-based Business Solutions

Supports interworking with solutions such as the IP contact center, groupware, video conference call, etc.
Provides the OpenAPI to allow interworking with third party solutions, helping the customer's business

Various Application Solutions

Interworking with various application solutions such as voice mail solutions with a built-in board, integrated with various applications, etc.

Unified Web Management

- Exports and imports databases
- Provides the Export function that exports the databases of a telephone, Voice Mail, and Auto Attendant
- Provides the Import function that imports the databases of a telephone, Voice Mail and Auto Attendant
- Uploads a system package through the Web with the Package Upload function
- Telephone setting functions
- Voice Mail/Auto Attendant setting functions

Specifications

Product	Specifications
Switching Method	IP
Basic Line Capacity	4 Trunk + 4 Digital + 8 Analog
Basic CPU	ARM11 375 MHz Dual Core
Memory	128 MB SDRAM, 512 MB NAND Flash
Input power	- AC 200–240 V, 3 A, 60 Hz

- DC 48 V, 4 A			
Output power	- DC -55 V, 1.7 A		
- DC +5 V, 4 A			
- DC -54 V, 0.4 A			
Dimensions	425 (W) x 315 (D) x 87 (H) mm		
Power	135 Watts		
Maximum Line Capacity	Trunk	Analog trunk	28
PRI trunk	30		
SIP trunk	8		
SPNet port	8		
Station	Single Line Telephone	48	
Digital phone	36		
Samsung IP phone	32		
Samsung Wi-Fi phone	32		
SIP phone	32		
Others	AA port (G.711)	4	
VM port (G.711)	4		
MGI port (G.729)	8		
Available	Terminals	ITP-5114D, ITP-5121D, ITP-5112L, ITP-5100V	
WLAN	SMT-W5100 (mobile station)		
Digital Phone	DS-5000 series (DS-5014D, DS-5021D, DS-5038D)		
DS-4000 Series (DS-4018E, DS-4028E)			
DS-24SE, DS-24D			
AOM	DS-5064B AOM, DS-4014 AOM, ITP-5164B		
DS-4064 AOM, DS-24SE AOM			
- For AOM, 12 units can interwork with the BMP (MAIN part) of the	OfficeServ 7070 system, 12 units v		
Others	DPIM, Door phone		